

Environmental & Technical Services Limited

Unit 7 Millbrook Business Park, Hoe Lane,

Nazeing, Essex EN9 2RJ Tel: +44 (0)1992 899 440

Email: climatic@ets.co.uk Web: www.ets.co.uk



Specialist Suppliers to the Environmental Industry

HIRE CHAMBER SPECIFICATIONS

ETS Serial No.	1001-3		Useful Capacity (Litres)		130			
Chamber Type	Thermal Sho	Thermal Shock Manufacturer			ACS			
Model No.	CST 130/2T	CST 130/2T Manuf. Serial No.			TT00404			
Date of Manufacture	Date of Refurbishment				2024			
Internal Dimensions	614x500x425 mm (WxDxH)							
External Dimensions	1165x2025x2700 mm (WxDxH)							
Weight	1250KG							
Temperature Range	Upper Chamber +40°C to +220°C / Lower Chamber -80°C to +60°C							
Temperature Rate of	Thermal Shock							
Change	Basket Transfer 10 Seconds							
Humidity Range	n/a							
Altitude Range	n/a							
Power Supply Requirement	32AMP/ 3 Phase /		Compressed Air			n/a		
	+ N + E		Requirements					
Water Requirements			Drainage Requiren		ments	n/a		
	Condenser v	vater						
	2.8 m3/hr &	15°C						
Door Hanging (L/R)		Window		Υ	Size (mm)	W: 3V	V	H:300
Cable Entry Ports	50mm Diameter through the Roof							
(No. size & location)								
Type of Controller	ACS							
Additional Instruments	No							
Castors (Y/N)	N		No. of Shelves		1			
Type of Cooling System	Cascade		Refrigerant Used		R4O4A & R23			
Additional Notes								



E&OE











